



Manufacturer of pneumatic impact tools and hydraulic tools for mines, quarries, construction industry, steelworks and foundries.

TECHNICKÉ ÚDAJE – TECHNISCHE DATEN – TECHNICAL DATA



SEK 2-1CP PNEUMATIC CHIPPING HAMMER

APPLICATION

The chipping hammer is a versatile tool. It is used in construction work (light chipping and breaking, slotting, cleaning), foundries (degating castings, removing risings) and in stonework (wedging, cutting of inscriptions, sculpture, etc.).

Technical data and main dimensions	ISO Unit	SEK 2-1CP
Weight	kg	2,3
Impact energy	J	1,75
Impact rate	Hz	84
Air consumption	m ³ min ⁻¹	0,32
Operating air pressure	MPa	0,2 – 0,6
Effective value of weighted acceleration	m.s ⁻²	3,14
Measured sound power level	dB	98,1
Guaranteed sound power level	dB	99
Length x Width	mm	220 x 150
Supply hose	mm	Js 13
Connecting thread		G 1/2"(d) or Socket Js 13
Tool shank size	mm	Ø 12,7 - # 11 x 45
Ordering code		9470-601

www.permon.cz
e-mail : prodej@permon.cz
e-mail : export@permon.cz

Roztoky 217, 270 23 Křivoklát, Česká republika
pro ČR, SR - for the Czech Rep. and SK
pro ostatní země - für andere Gebiete - for other territories
v : 4.2023

T: + 420 313 521 548
T: + 420 313 521 563