



Manufacturer of pneumatic impact tools and hydraulic tools for mines, quarries, construction industry, steelworks and foundries.

## TECHNICKÉ ÚDAJE – TECHNISCHE DATEN – TECHNICAL DATA



# SEK 2-1CP; SEK 2-1CR PNEUMATIC CHIPPING HAMMER

### APPLICATION

The chipping hammer is a versatile tool. It is used in construction work (light chipping and breaking, slotting, cleaning), foundries (degating castings, removing risings) and in stonework (wedging, cutting of inscriptions, sculpture, etc.).

Technical data and main dimensions	ISO Unit	SEK 2-1CP	SEK 2-1CR
Weight	kg	2,3	2,45
Impact energy	J	1,75	
Impact rate	Hz	84	
Air consumption	m <sup>3</sup> min <sup>-1</sup>	0,32	
Operating air pressure	MPa	0,2 – 0,6	
Effective value of weighted acceleration	m.s <sup>-2</sup>	3,14	
Measured sound power level	dB	98,1	
Guaranteed sound power level	dB	99	
Length x Width	mm	220 x 150	230 x 150
Supply hose	mm	Js 13	
Connecting thread		G 1/2"(d) or Socket Js 13	G 1/4"(D)
Tool shank size	mm	Ø 12,7- # 11x45	Ø 12,6- #10,6x50
Ordering code		9470-601	9470-611

www.permon.cz  
e-mail : prodej@permon.cz  
e-mail : export@permon.cz

Roztoky 217, 270 23 Křivoklát, Česká republika  
pro ČR, SR - for the Czech Rep. and SK

pro ostatní země - für andere Gebiete - for other territories

T: + 420 313 521 548

T: + 420 313 521 563

v : 4.2023