



Výrobce hydraulického nářadí a  
pneumatického příklepného vrtacího nářadí pro  
doly, lomy, stavebnictví a slévárenství.

## VÍCEÚČELOVÉ HADICE – VZDUCH, VODA



Vhodná pro dopravu stlačeného vzduchu se stopami oleje a pro vodu o provozním tlaku 15Bar. Vhodná pro použití ke kompresorům a veškerým zařízením na stlačený vzduch v průmyslu a stavebnictví. Průběžné značení bílou barvou.

**Teplotní rozsah:** -35°C / +70°C.

**Bezpečnostní faktor:** 3 : 1

**Duše:** SBR, černá, hladká, vhodná pro vzduch s obsahem oleje.

**Výztuž:** Textilní příze, ovin

**Obal:** SBR, černý, hladký, otisk textilu na povrchu.

Objednací číslo	Ø Vnitřní (mm)	Tloušťka stěny (mm)	Ø Vnější (mm)	Max. Provozní tlak (Bar)	Počet výztuží	Min. Poloměr ohybu (mm)	Délka svitku (m)
272108	13	3,5	20	15	2	100	25 nebo 50
272207	16	5	26	15	2	160	25 nebo 50
272208	20	5	30	15	2	200	25 nebo 50
272200	25	4,5	34	15	2	250	25 nebo 50

www.permon.cz

e-mail : prodej@permon.cz

e-mail : export@permon.cz

Roztoky 217, 270 23 Křivoklát, Česká republika

pro ČR, SR

pro ostatní země

v : 09.2020

T: + 420 313 521 567

T: + 420 313 521 563



Manufacturer of pneumatic impact tools and hydraulic tools for mines, quarries, construction industry, steelworks and foundries.

## MULTI-PURPOSE HOSES - AIR/WATER



Suitable for the delivery of lubricant-laden compressed air and water at a working pressure of 15 bar. For use in industry and commerce. Continuous inkjet, white letters.

**Temperature range:** -35°C / +70°C.

**Safety factor:** 3 : 1

**Tube:** Synthetic rubber, black, suitable for oil-laden air, smooth.

**Reinforcement:** Textile spiral.

**Cover:** Synthetic rubber, black, resistant to ozone and weather, smooth.

Article number	Ø Internal (mm)	Wall width (mm)	Ø External (mm)	Max. Work. pressure (Bar)	Number of inserts	Min. Bending radius (mm)	Coil length (m)
272108	13	3,5	20	15	2	100	25 or 50
272207	16	5	26	15	2	160	25 or 50
272208	20	5	30	15	2	200	25 or 50
272200	25	4,5	34	15	2	250	25 or 50

[www.permon.cz](http://www.permon.cz)

e-mail : [prodej@permon.cz](mailto:prodej@permon.cz)

e-mail : [export@permon.cz](mailto:export@permon.cz)

Roztoky 217, 270 23 Křivoklát, Česká republika

for the Czech Rep. and SK

for other territories

v: 06.2020

T: + 420 313 521 567

T: + 420 313 521 563