



Manufacturer of pneumatic impact tools and hydraulic tools for mines, quarries, construction industry, steelworks and foundries.

TECHNICKÉ ÚDAJE – TECHNISCHE DATEN – TECHNICAL DATA



BKA 30 Breaking Hammer

APPLICATION

The breaking hammer is a versatile tool. It is designed for breaking up low to medium strength rock and material (concrete, bituminous roadways, masonry etc.). Its design and weight favors use in downwards-horizontal or sloping direction.

Technické údaje – Technische data – Technical data	ISO	BKA 30-B	BKA 30-C	BKA 30-E	BKA 30-F
Hmotnost - Gewicht - Weight	kg	32			
Energie úderu - Schlagenergie - Impact energy	J	95			
Frekvence úderů - Schlagfrequenz – Impact frequency	Hz	22			
Spotřeba vzduchu - Luftverbrauch – Air consumption	m ³ .min ⁻¹	1,8			
Garantovaná hladina akustického výkonu L _{WA} – Garantierter Lärmpegel L _{WA} – Guaranteed noise level L _{WA}	dB	107			
Vážená hodnota vibrací - Vibrationspegel - Vibration level	m.s ⁻²	5,3			
Délka - Länge - Length	mm	735			
Šířka - Breite - Width	mm	441			
Provozní přetlak vzduchu - Betriebsluftdruck - Oper. air pressure	MPa	0,4 – 0,7			
Stopka nástroje - Einsteckende – Tool shank	mm	#28x 160	#32x 160	#32x 152	#28x 152
Přívodní hadice - Luftzufuhrschlauch – Air supply hose	mm	Js 16			

www.permon.cz
e-mail : prodej@permon.cz
e-mail : export@permon.cz

Roztoky 217, 270 23 Křivoklát, Česká republika
pro ČR, SR - for the Czech Rep. and SK
pro ostatní země - für andere Gebiete - for other territories
v : 3.2023

T: + 420 313 521 548
T: + 420 313 521 563